



## OAK HAMPSHIRE

The rosy blonde nuances in this exclusive, single-strip floor from the European Naturals Collection are enhanced by an even colour variation between planks. The wearing surface is taken from a single piece of wood for a lively, organic expression. The silk matt lacquer finish gives the floor a polished look and enhances the natural character of the wood.

### PRODUCT DETAILS

<b>Article Number</b>	151L87EK09KW240
<b>Surface treatment</b>	Matt lacquer
<b>Dimensions</b>	2420 x 187 x 15 mm
<b>Weight per Package</b>	22 kg
<b>Area per Package</b>	2.72 m <sup>2</sup>
<b>Area Per Board</b>	0.453 m <sup>2</sup>

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Lively (Country)
<b>Range</b>	Kährs Original
<b>Collection</b>	European Naturals Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Natural
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	3,5 mm
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	15 mm
<b>Installation method</b>	Floating, Glue-down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>		>500 kg/m <sup>3</sup>
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m2K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

