



OAK NOUVEAU WHITE

The soft white stain on this single-strip, white oak floor from the Classic Nouveau Collection has an even expression, lightly peppered with small knots and cracks. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS

| | |
|---------------------------|---------------------------|
| Article Number | 151L8AEK1DKW240 |
| Surface treatment | Matt lacquer |
| Design features | Bevelled 4-sided, Brushed |
| Dimensions | 2420 x 187 x 15 mm |
| Weight per Package | 22 kg |
| Area per Package | 2.72 m ² |
| Area Per Board | 0.453 m ² |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticable color change over time.

CERTIFICATES

FACTS

| | |
|-----------------------------|----------------------------|
| Wood Species | Oak |
| Board | 1-strip |
| Grading | Lively (Country) |
| Range | Kährs Original |
| Collection | Classic Nouveau Collection |
| Resandable | 2-3 times |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 3,5 mm |
| Core material | Pine/Spruce lamella |
| Thickness | 15 mm |
| Installation method | Floating, Glue-down |
| Surface Colour | White 1D |

TECHNICAL PROPERTIES

| | | |
|--|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |

CERTIFICATES



AIR RESOURCES BOARD



BYGGAUTSBEGRÄNKNINGEN



FloorScore Certified