



OAK HORIZON

This single-strip oak floor from the Lux Collection features a misty white transparent stain, which allows distinctive gradations in the wood to come through. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AEKC4KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Ultra matt lacquer	Board	1-strip	Minimum Mean Density kg/m³		>500 kg/m³
Design features	Microbevelled 4-sided, Brushed	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	22 kg	Collection	Lux Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.72 m²	Resandable	2-3 times	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.453 m²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION	All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.		Brinell Value	3,7	Thermal Resistance R-Value	.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3,5 mm			
		Core material	Pine/Spruce/Alder			
		Thickness	15 mm			
		Installation method	Floating, Glue-down			
		Surface Colour	White			

COLOUR CHANGE

Stained product - noticeable color change over time

CERTIFICATES

CERTIFICATES



AIR RESOURCES BOARD



BYGGAUTOMATISERINGSBUREÅN

