



## OAK VERONA

This 2-strip oak floor from the European Naturals Collection has a distinct colour variation, which ranges from malted milk highlights to toffee brown lowlights. The marbled grain of the timber is punctuated with naturally occurring knots.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
<b>Article Number</b>	152N38EK04KW240	<b>Wood Species</b>	Oak	<b>Moisture content</b>	EN13183	7%±2%
<b>Surface treatment</b>	Ultra matt lacquer	<b>Board</b>	2-strip	<b>Minimum Mean Density kg/m<sup>3</sup></b>		>500 kg/m <sup>3</sup>
<b>Design features</b>	Brushed	<b>Grading</b>	Variation (Town)	<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Dimensions</b>	2423 x 200 x 15 mm	<b>Range</b>	Kährs Original	<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Weight per Package</b>	23 kg	<b>Collection</b>	European Naturals Collection	<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Area per Package</b>	2.91 m <sup>2</sup>	<b>Resandable</b>	2-3 times	<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Area Per Board</b>	0.485 m <sup>2</sup>	<b>Natural/Stained</b>	Natural	<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>DETAIL DESCRIPTION</b>	Naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes medium sound and black knots. Knots may vary in size and numbers.		<b>Brinell Value</b>	3,7	<b>Thermal Resistance R-Value</b>	.11 (m2K/W)
<b>COLOUR CHANGE</b>	Some muting of colour variation to medium, straw brown.		<b>Joint</b>	Woodloc® 5S	<b>Biological Durability</b>	EN350-2 Class 1
		<b>Floor heating</b>	Yes	<b>CARB2</b>		Compliant
		<b>Warranty</b>	30 years			
		<b>Wear-layer material</b>	Hardwood			
		<b>Wear-layer thickness</b>	3,5 mm			
		<b>Core material</b>	Pine/Spruce lamella			
		<b>Thickness</b>	15 mm			
		<b>Installation method</b>	Glue-down, Floating			

### CERTIFICATES



floor score certified