



OAK SHORE

The mineral grey notes in this single-strip oak floor from the Lux Collection are awash with subtle earth tones, eloquently complemented by the ultra-matt lacquer finish. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AEKE4KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Ultra matt lacquer	Board	1-strip	Minimum Mean Density kg/m³		
Design features	Microbevelled 4-sided, Brushed	Grading	Lively (Country)			
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	22 kg	Collection	Lux Collection	Formaldehyde Emission	EN717-1	E1
Area per Package	2.72 m²	Resandable	2-3 times	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	0.453 m²	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
DETAIL DESCRIPTION	All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all	Brinell Value	3,7	Thermal Conductivity	EN12664	0,14 W/mK
		Joint	Woodloc® 5S	Thermal Resistance R-Value		.11 (m2K/W)
		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Warranty	30 years	CARB2		Compliant
		Wear-layer material	Hardwood			
		Wear-layer thickness	3,5 mm			
		Core material	Pine/Spruce/Alder			
		Thickness	15 mm			
		Installation method	Floating, Glue-down			
		Surface Colour	Grey			

COLOUR CHANGE

Stained product - noticeable color change over time

ERTIFICATES

