



# CHARCOAL LIGHT PLANK

Charcoal Light plank is inspired by dried raisins soaked in hot chocolate. The deep musty stain in combination with rustic wood gives a magic expression with an ultramatt finish.

## PRODUCT DETAILS

<b>Article Number</b>	151N9AEKS4KW200
<b>EAN Code</b>	7393969048323
<b>Surface treatment</b>	Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles.
<b>Design features</b>	Brushed, Microbevelled 4-sided
<b>Dimensions</b>	187 x 2000 mm
<b>Weight per Package</b>	18.256 kg
<b>Area per Package</b>	2.24 m <sup>2</sup>
<b>Area per pallet</b>	100.8 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

## DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

## COLOUR CHANGE

Stained product - noticeable color change over time.

## FACTS

<b>Wood Species</b>	Oak
<b>Design</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Original
<b>Collection</b>	Beyond Retro Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear Layer Thickness</b>	3.5 mm
<b>Core material</b>	Pine/Spruce/Alder
<b>Backside material</b>	Spruce Veneer
<b>Thickness</b>	15 mm
<b>Installation method</b>	Floating, Glue-down
<b>Surface Colour</b>	Brown
<b>LRV</b>	13

## TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.11 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	
<b>Slipperiness</b>	CEN/TS15676	NPD

## Other products in this collection




Urban Brown Strip



Loft White Strip



Loft White Plank



Charcoal Light Strip




Frosted Oat Plank




Urban Brown Plank




Frozen Hazelnut Plank



Pearl Grey Plank




Frosted Oat Strip



Charcoal Light Plank



Pearl Grey Strip



Frozen Hazelnut Strip

## CERTIFICATES



## Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*